

DEPARTMENT OF TRANSPORTATION

STATE OF GEORGIA

INTERDEPARTMENTAL CORRESPONDENCE

FILE Pavement Design OFFICE Materials and Testing
Forest Park, Georgia
DATE August 14, 2017

FROM  Monica L. Flournoy, P. E., State Materials Engineer

TO Marc Mastronardi, P. E., Director of Construction

SUBJECT **Extension of Guidelines for Standard Pavement Sections for Minor Projects**

This document provides an extension to the Guidelines for Pavement Sections for Minor Projects - Addendum, dated September 18, 2013.

A 1.50-inch layer of 12.5mm Superpave may be substituted for the 1.25-inch layer of 9.5mm Superpave when the 24-hour truck percentage is greater than 10% but less than 20%, only if the Average two way ADT is less than or equal to 10,000 and the calculated TDL is less than the maximum TDL listed in Table A.

The guidelines should also be used for pavement work constructed by permit within the GDOT right-of-way.

Overlay designs are not covered by this guideline.

The above guidelines, once approved, are for immediate implementation. Pavement designs meeting the criteria of these Extended Minor Project Guidelines will not require review and approval by the State Pavement Engineer or the Pavement Design Committee (PDC).

However, projects with 24-hour truck percentage greater than 20% that have an average two way ADT less than or equal to 10,000 and the calculated TDL less than the maximum TDL listed in Table A may be submitted for review and approval by the State Pavement Engineer.

If additional information is needed, please contact Ian Rish, P.E., of the Pavement Management Branch at 404-608-4849 (Direct) or 404-608-4770 (Main).

Concur:




Director of Engineering

8/28/2017

Date

Approve:



Chief Engineer

8/29/17

Date

MLF: JTR: IDR